



## SmartClass™ Fiber

### OLT-85 and -85P Inspection-Ready Optical Loss Test Sets

The SmartClass Fiber OLT-85 and -85P combine a fiber inspection microscope, optical power meter (OPM), and optical light source (OLS) in one versatile test instrument. The compact instrument provides the essential fiber tests—inspection, power, insertion loss, and continuity—for multimode and single-mode networks.

JDSU merges a highly accurate optical power meter and up to four light sources in one compact test instrument to create a test set that precisely and automatically measures insertion loss error-free. The ultra-sensitive power meter combined with stabilized light sources can measure fiber loss up to 85 dB for single-mode and up to 65 dB for multimode. Its specific wavelength combinations make it ideal for qualifying and certifying long-haul, metro, and access telecommunication networks as well as data center and local area networks.

Adding the P5000i digital analysis microscope to the OLT-85 and -85P lets users check fiber end-face quality with pass/fail acceptance results at the push of a button.

The OLT-85P features an integrated patch-cord microscope (PCM) for added value and improved workflow efficiency.

Threshold settings for pass/fail indications and the intuitive touch screen interface transforms users into instant fiber experts without the need for special training. Automatic functions, such as Auto- $\lambda$  and real-time Multi- $\lambda$  functionalities avoid handling errors and significantly speed up test time. The OLT-85 and -85P are fully compatible with other members of the SmartClass Fiber family (OLS, OLP, and ORL) that also have these automatic functions.

Users can easily save test results (power, insertion loss, and fiber inspection) with a real-time stamp to generate on-board certification reports. FiberChekPRO™ PC software enables users to easily upload test results to a PC for post-processing.

The OLT-85 and -85P inspection-ready optical loss test sets can be used anywhere today's fiber technicians go, up poles or down holes. Technicians gain ultimate flexibility and performance from this powerful easy-to-use solution that can instantly transform any technician into a fiber expert.

#### Key Benefits

- Complete jobs faster, correctly, and on time—the first time—with this unique integrated fiber inspection microscope, optical power meter, and optical light source
- Battery-operated, field-portable instrument provides a full day of autonomy
- Ability to transfer data and to control remotely via USB or Ethernet interface
- Shielded housing for extreme accuracy in RF environments
- Rugged, weather-proof design ideal for outdoor use

#### Key Features

- Optical power meter with 900 settable wavelengths and high dynamic range accuracy for testing multimode and single-mode fiber
- Dual and quad light source versions with encircled flux (EF)-compliant launch conditions at 850 nm
- In-service loss test option
- 3.5" color touch screen with integrated stylus
- Automated pass/fail fiber inspection analysis with optional P5000i microscope; a version is available with an integrated PCM
- Onboard fiber inspection and test results storage with time stamp

**Specifications**

	<b>OLT-85 (2325/01)</b> <b>OLT-85P (2326/01)</b>	<b>OLT-85 (2325/05)</b> <b>OLT-85P (2326/05)</b>
<b>Operating Modes</b>	Power Meter, Light Source, Loss Test Set	
<b>Power Meter</b>		
Detector type	InGaAs	
Power measurement range	-85 to +15 dBm	
Max. permitted input level	+15 dBm	
Intrinsic uncertainty <sup>1</sup>	±0.13 dB (±3%)	
Automatic offset nulling	Yes	
Wavelength range/settings	800 to 1700 nm, in 1 nm steps	
Calibrated wavelengths	850, 980, 1300, 1310, 1490, 1550, 1625 nm	
Display resolution	0.01 dB/0.001 μW	
Measurement units	dB, dBm, W	
Power meter functions	Absolute, relative, pass/fail	
Auto functions <sup>2</sup>	Auto-λ	Auto single-wavelength detection
	Multi-λ	Auto multi-wavelength detection
Tone detection	270 Hz, 1 kHz, 2 kHz	
Optical interfaces	2.5 mm UPP for FC, SC, ST, DIN, and E2000 connector types	
	1.25 mm UPP for LC and MU connector types (optional)	
Warm-up time	None, Instant-On	
<b>Light Source</b>		
Nominal wavelengths <sup>3</sup>	1310/1550 nm	MM 850/1300 nm
		SM 1310/1550 nm
Spectral width	<5 nm	MM 50/170 nm
		SM 5/5 nm
Launch conditions	EF compliant at 850 nm	
Output power (settable in 0.01 dB steps)	0 to -3 dBm	MM -20 to -23 dBm
		SM 0 to -3 dBm
Stability <sup>4</sup> 15 min/8 hr	0.02/0.2 dB	
Source modes	CW, tone, Auto-λ <sup>5</sup> , Multi-λ <sup>5</sup>	
Tone generator	270 Hz, 1 kHz, 2 kHz	
Optical interfaces	PC connector with interchangeable SC, FC, ST adapters	
<b>General</b>		
Laser class	Class 1 laser product (IEC 60825-1:2007)	
Display	3.5-in color LCD touch screen, 4:3 ratio	
Data readout	Via USB interface	
Remote control capability	Via USB or Ethernet	
Inspection functions	Live, freeze, store end-face image, auto pass/fail	
Data storage	Up to 10,000 test results time stamp; Abs. and rel. power results and inspection images (jpg)	
Electrical interfaces	USB 2.0 (2 x host, type A, 1 x device, Micro-B)	
Power source	AC adaptor, 8x AA alkaline, or rechargeable LiON battery pack (option)	
Power mode	Active, Auto-Off (programmable)	

<b>General</b>		
Battery life (continuous operation)	>10 hr (LiON)/>8 hr (alkaline)	
Dimension (H x W x D) and Weight	OLT-85	208 x 112 x 64 mm (8.2 x 4.4 x 2.5 in) 750 g (1.6 lb)
	OLT-85P	208 x 153 x 64 mm (8.2 x 6.0 x 2.5 in) 850 g (1.85 lb)
Operating temp. range	-5 to +45°C (23 to 113°F)	
Storage temp. range	-25 to +55°C (-13 to 131°F)	

**Ordering Information**

OLT-85 and OLT-85P Optical Loss Test Sets include:

- SmartClass Fiber instrument
- SC2 Soft Shoulder Case, for SCF tools
- Universal optical adapter UPP 2.5 mm for power meter
- Optical adapters for light source SC-type (mounted) and FC-type (interchangeable)
- Quick Start manual and safety instructions
- Alkaline batteries (8)

<b>Description</b>	<b>Part Number</b>
OLT-85 Loss Test Set 1310/1550 nm, PC	2325/01
OLT-85 Loss Test Set 850/1300/1310/1550 nm, PC	2325/05
OLT-85P Loss Test Set 1310/1550 nm, PC, with integrated patch-cord microscope (PCM)	2326/01
OLT-85P Loss Test Set 850/1300/1310/1550 nm, PC, with integrated patch-cord microscope (PCM)	2326/05
<b>Options and Accessories</b>	
P5000i digital analysis microscope with 4 tips	FBP-SD101
RBP2 Rechargeable LiON battery pack 3.7V/20W	2305/90.02
PS4 power supply, 12V, 2 A	2305/90.01
RBP2 Rechargeable LiON battery pack with PS4 power supply	2305/90.04
UC4 hands-free carrier	2128/01
SC2 soft shoulder case	2128/03
FC-type optical adapter	2155/00.05
SC-type optical adapter	2155/00.26
ST-type optical adapter	2155/00.32
USB cable USB-A to Micro-USB	K 807
UPP adapter 2.5 mm type — SC/FC/ST/DIN	2307/90.02
UPP adapter 1.25 mm type — LC/MU	2307/90.03

1. Under reference conditions: at 1310 nm ±1 nm, -20 dBm (CW), 23°C ±3K, 9 μm test fiber with SC/PC ceramic connector  
 2. Works in conjunction with OLS-3x, OLS-5x, OLS-85, OLT-85, and ORL-85  
 3. ±20 nm  
 4. Between -5 to +45°C with ΔT = ±0.3 K after a 20-minute warm-up  
 5. Works in conjunction with OLP-3x, OLP-55, OLP-85, OLT-85, and ORL-85



**North America**  
**Latin America**  
**Asia Pacific**  
**EMEA**

Toll Free: 1 855 ASK-JDSU  
 Tel: +1 954 688 5660  
 Tel: +852 2892 0990  
 Tel: +49 7121 86 2222

(1 855 275-5378)  
 Fax: +1 954 345 4668  
 Fax: +852 2892 0770  
 Fax: +49 7121 86 1222